

## Highlights:

---

- Lightweight class-D amplifier
- Advanced protection circuit
- XLR input & linkthrough connections with gain control & HPF switch
- Terminal block output connections
- High-pass filter switch



## Product information:

---

The CAP series are professional 100V multi-channel power amplifiers. The CAP248 offers the two channels and has an output power of 480 Watt. This way, a flexible solution is created for multi-zone audio distribution systems with two independent zones. They are designed as no-nonsense amplifiers with only the necessary controls and connections, which creates great simplicity in use and installation. A high efficiency and reliability of the devices is achieved by using switching power supplies in combination with Class-D amplifier technology. A temperature controlled fan constantly keeps all parts within the right operation range, while avoiding excessive buzz. A built-in multipurpose protection circuit protects against DC malfunction, Short circuit, overheating, overload and limits the signal when necessary. The input connections are performed using balanced XLR connectors and Link output connectors are provided for link through to other amplifiers. Besides, a high-pass filter switch (400 Hz) and a Gain adjustment potentiometer are provided for each channel. The output connections are performed using reliable terminal block connectors and this all is housed into a solid constructed, double rack space (2 HE) 19" rack mounting housing.

## Applications:

---

- Bars & Restaurants
- Education
- Corporate
- Clubs
- Retail

## System specifications:

RMS/AES power handling		2 x 480 W
Frequency	Response ( $\pm 3$ dB)	50 Hz - 22 kHz
Signal / Noise		> 100 dB
THD+N (@ 1 kHz)		< 0.3% (1/2 Rated Power)
Crosstalk (@ 1 kHz)		< 80 dB
Technology		Class-D
Power	Supply	Switching mode
	Source	230 ~ 240 V AC / 50 Hz
Inputs	Sensitivity	-0.5 dB ~ 10.5 dB
	Impedance	10 k $\Omega$ balanced
	Connector	XLR female with Male Linkthrough
Outputs	Voltage / Impedance	100 V / 21 $\Omega$
	Connector	4-pin Euro Terminal Block (Pitch - 5.08 mm)
Common mode rejection ratio		70 dB
Protection		DC Short circuit
		Over heating
		Over load
		Signal limiting
Cooling		Temperature controlled fan
Operating temperature		0° ~ 40° @ 95% Humidity

## Product Features:

Dimensions		482 x 88 x 420 mm (W x H x D)
Weight		7.500 kg
Mounting		19"
Unit height		2 HE
Construction		Steel
Colours		Black
Accessories	Included	2 x 4-pin Euro Terminal Block outputs connector
	Optional	CPE100 Rack mount handles

## Shipping & Ordering:

---

Packaging	Cardboard box
Shipping weight & volume	10.8 kg - 0.046 Cbm

## Architects' and Engineers' Specifications:

---

The Amplifier shall be a constant voltage 100 Volt type, containing four independent controllable amplifier channels with an output power of 2 x 480 Watt. The construction shall be transformerless, using Class-D Amplifier technology and powered by a switching power supply. Each channel shall have integrated circuitry to protect against short-circuits or mismatched loads and over-heating. The operating temperature for each channel shall be continuously monitored and a speed-controlled fan will keep it within the operating range while minimising the acoustic noise. Additionally, the load shall be protected against DC faults and a clip limiter shall automatically reduce the input gain at onset of distortion.

The front panel shall contain an AC power switch accompanied by a blue power indicator LED and channel operation indicator LED's. Two green signal LED's indicating the presence of an input signal and it's level exceeding the -20 dB level, a clip LED indicating the channel operation at maximum level and a protection LED indicating any fault detected shall be provided for each channel.

All connections shall be made on the rear panel of the unit. The signal input connections shall be balanced and performed using female XLR connectors with male XLR connectors allowing signal link through to other channels or amplifiers. A gain control potentiometer shall be provided to adjust the input sensitivity within a range of -0.5 dB to 10.5 dB, and a switch shall allow the enabling / disabling of a highpass filter with a roll off frequency of 400 Hz.

The output connections shall be performed using 4-pin Terminal block connectors, allowing connectivity of multiple loudspeaker lines on one amplifier channel.

The amplifier shall operate on a 230~240 V AC / 50 Hz mains network and shall be equipped with a removable power cord having a standard shuko (CEE 7/7) AC plug. The connector on the amplifier chassis shall be a fused IEC C14 type.

The amplifier chassis shall be a two rackspace steel constructed 19" housing. Depth from mounting surface to rear supports shall be 420 mm and the weight shall not exceed 7.5 Kg.

