



### Features

- **Designed for video production and broadcast (ENG/EFP) audio acquisition**
- **Short length ensures mic stays out of the shot – even when used with compact digital cameras**
- **Provides the narrow acceptance angle desirable for long-distance sound pickup**
- **Smooth, natural-sounding on-axis audio quality**
- **Offers the convenience of battery or phantom power operation**
- **Rugged design and construction for reliable performance**
- **Switchable 80 Hz high-pass filter minimizes pickup of undesired low-frequency sounds**

### Description

The AT897 is a fixed-charge condenser microphone with a line + gradient polar pattern. It is designed for video production, broadcast (ENG/EFP) audio acquisition, wildlife recording and high-quality sound reinforcement.

The microphone requires 11V to 52V phantom power or a 1.5V AA battery for operation. A battery need not be in place for phantom power operation.

The microphone's highly directional polar pattern provides a narrow acceptance angle along with crisp, intelligible audio reproduction desirable for long-distance sound pickup.

The output of the microphone is a 3-pin XLR-M type connector.

A switch permits choice of flat response or low-frequency roll-off (via integral 80 Hz high-pass filter) to help control undesired ambient noise.

The microphone is enclosed in a rugged housing. The included AT8405a stand clamp permits mounting on any microphone stand with 5/8"-27 threads. A windscreen, two o-rings, a battery and a protective carrying case are also included.

### Operation and Maintenance

The AT897 requires 11V to 52V phantom power or a 1.5V AA battery for operation. A battery need not be in place for phantom power operation.

To install the battery, unscrew the lower section of the microphone body, just below the nameplate. Insert a fresh 1.5V AA battery in the handle compartment ("+" end up), then reassemble the microphone. Alkaline batteries are recommended for longest life. Remove the battery during long-term storage.

Output is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot" – positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

An integral 80 Hz high-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The roll-off position reduces the pickup of low-frequency ambient noise (such as traffic, air-handling systems, etc.), room reverberation and mechanically coupled vibrations. To engage the high-pass filter, use the end tip of a paperclip or other small pointed instrument to slide the switch toward the "bent" line.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

**Note:** To use the microphone with a camera-mount microphone holder whose diameter is too large to secure the microphone, slide the two supplied o-rings onto the microphone handle, spaced so that one fits just in front of, and the other fits just behind, the rubber nubs inside the microphone holder. When the top of the microphone holder is closed and tightened down, the o-rings should hold the microphone securely in place.

To reduce the environmental impact of a multi-language printed document, product information is available online at [www.audio-technica.com](http://www.audio-technica.com) in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site [www.audio-technica.com](http://www.audio-technica.com) dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: [www.audio-technica.com](http://www.audio-technica.com).

Para reduzir o impacto ecológico de um documento impresso de várias linguas, a Audio-Technica providência as informações dos seus produtos em diversas linguas na [www.audio-technica.com](http://www.audio-technica.com).

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito [www.audio-technica.com](http://www.audio-technica.com).

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: [www.audio-technica.com](http://www.audio-technica.com).

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: [www.audio-technica.com](http://www.audio-technica.com).

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 [www.audio-technica.com](http://www.audio-technica.com) 的官方網頁上選擇所屬語言及瀏覽。

[www.audio-technica.com](http://www.audio-technica.com) 的官方网页上选择所属语言和浏览。

자원절약, 환경보호를 위해 국문 사용 설명서는 인쇄하지 않았습니다. 제품정보는 [www.audio-technica.com](http://www.audio-technica.com) 에서 원하는 언어 선택 후에 다운로드 받으실 수 있습니다.

## Specifications


Element	Fixed-charge back plate, permanently polarized condenser
Polar pattern	Line + gradient
Frequency response	20-20,000 Hz
Low cut	80 Hz, 18 dB/octave
Open circuit sensitivity	Phantom: -40 dB (10.0 mV), (0 dB = 1 V/Pa, 1 kHz) Battery: -41 dB (8.9 mV), (0 dB = 1 V/Pa, 1 kHz)
Impedance	Phantom: 250 ohms Battery: 300 ohms
Maximum input sound level	Phantom: 129 dB SPL (1 kHz at 1% THD) Battery: 115 dB SPL (1 kHz at 1% THD)
Dynamic range	Phantom: 112 dB (1 kHz at Max SPL) Battery: 98 dB (1 kHz at Max SPL)
Signal-to-noise ratio	77 dB (1 kHz at 1 Pa, A-weighted)
Phantom power requirements	11-52V DC, 2 mA
Battery type	1.5 V DC R6/LR6, AA
Battery current / life	0.4 mA / 1200 hours (alkaline)
Switch	Low cut: on/off
Weight	145 g (5.1 oz)
Dimensions	279 mm (11") long, 21 mm (0.83") head diameter
Output connector	Integral 3-pin XLR-M type
Audio-Technica case style	SG2
Included accessories	AT8405a stand clamp for 5/8"-27 threaded stands, 5/8"-27 to 3/8"-16 threaded adapter, AT8134 windscreen, Battery (AA/R6), O-ring×2, Protective carrying case

• 1 Pascal = 10 dynes/cm<sup>2</sup> = 10 microbars = 94 dB SPL

For product improvement, the product is subject to modification without notice.




## Polar pattern



LEGEND

200 Hz - - - - - 5 kHz .....  
1 kHz ——— 8 kHz - - - - - SCALE IS 5 DECIBELS PER DIVISION

## Frequency response



LEGEND

— 0°, 50 cm      - - - - - 0°, 50 cm, Low cut

Warranty (Please be sure to read the notes below.)

For USA Only

End-User LIMITED WARRANTY information for the USA is available at [www.audio-technica.com/usawarranties](http://www.audio-technica.com/usawarranties). You may also contact Audio-Technica U.S., Inc. to request a written copy of the Limited Warranty at 1-330-686-2600 or via mail at 1221 Commerce Drive, Stow, OH 44224.

Audio-Technica Corporation

2-46-1 Nishi-naruse, Machida, Tokyo 194-8666, Japan

©2021 Audio-Technica Corporation

Global Support Contact: [www.at-globalsupport.com](http://www.at-globalsupport.com)

Made in Japan

P51973-3 142311671-02-04 ver.4 2021.09.01