

### DESCRIPTION

The WM-5265 Wireless Microphone employs an dynamic microphone capsule and is suitable for any applications. Thanks to the PLL-synthesizer system, 64 different operating frequencies are made available. A high output power ensures stable radio signal transmission.

### SPECIFICATIONS

|                          |                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------|
| Microphone Element       | Dynamic microphone unit: Unidirectional                                                                          |
| Modulation               | Frequency modulation                                                                                             |
| Frequency Range          | 576 – 937.5 MHz*, UHF                                                                                            |
| Channel Selectable       | 64 channels (the number of channels may differ from country to country)                                          |
| RF Carrier Power         | Less than 50 mW (Factory preset 10 mW ERP)                                                                       |
| Tone Frequency           | 32.768 kHz                                                                                                       |
| Oscillator               | PLL synthesized                                                                                                  |
| Maximum Input Level      | 132 dB SPL                                                                                                       |
| Maximum Deviation        | ±40 kHz                                                                                                          |
| Audio Frequency Response | 100 Hz – 15 kHz                                                                                                  |
| Dynamic Range            | 95 dB or more (with WT-5800)                                                                                     |
| Battery                  | WB-2000 rechargeable battery (option) or AA alkaline dry cell battery                                            |
| Battery Life             | Approx. 13 h (when the WB-2000 rechargeable battery is used)<br>Approx. 10 h (when the alkaline battery is used) |
| Indicator                | Power/Battery lamps                                                                                              |
| Antenna                  | Built-in type                                                                                                    |
| Operating Temperature    | –10 °C to +50 °C (14 °F to 122 °F) (except battery)                                                              |
| Operating Humidity       | 30 % to 85 %RH (no condensation)                                                                                 |
| Finish                   | Resin, coating                                                                                                   |
| Dimensions               | ø50 × 229 mm (ø1.97" × 9.02")                                                                                    |
| Weight                   | 205 g (0.45 lb) (with battery)                                                                                   |
| Accessory                | Microphone holder W3/8" (with stand adapter) ...1, Screw driver ...1, Storage case ...1                          |
| Option                   | Battery charger: BC-5000-2, BC-5000-6, BC-5000-12<br>Ni-MH battery: WB-2000-2 (containing 2 pieces)              |

### APPEARANCE

