

Specifications

Amplifier	
Maximum output power*	160 W
Type	Class-D
Speaker	
Woofer	1 x 8" (200 mm) LF driver
Tweeters	4 x 2.75" (82 mm) MF drivers
Analog Audio Connections	
Line in	1 x XLR / ¼" TRS combo jack, balanced
Impedance	20 kΩ, balanced / 10 kΩ, unbalanced
Line out	1 x XLR, balanced
Impedance	470 Ω, balanced / 220 Ω, unbalanced
Mic 1 / 2 in	2 x ¼" TRS, balanced
Impedance	10 kΩ, balanced / 4.7 kΩ, unbalanced
Digital Audio Connections	
USB	Type A
SD / MMC	Up to 32 GB supported
File system	FAT 16, FAT 32
Format	MP3 (DBR & VBR)
Bit rates	32 – 320 kbps
Sample rates	32 kHz, 44.1 kHz, 48 kHz
Bluetooth**	
Frequency range	2402 MHz ~ 2480 MHz
Channel number	79
Version	Bluetooth spec 4.2 compliant
Output	4 dBm
Compatibility	Supports A2DP 1.2 profiles
Maximum communication range	15 m (without interference)
Loudspeaker System Data	
Frequency response***	55 Hz – 17 kHz (-10 dB)
Sound pressure level	Max. 106 dB SPL @ 1 m
Limiter	Optical
THD+N	< 1%
Equalizer	
High	±6 dB @ 10 kHz, shelving
Low	±6 dB @ 100 Hz, shelving

Battery	
Battery type	28 V, 5200 mAh, lithium battery
Battery life	4 - 6 hours
Battery charging time	8 - 10 hours
Power Supply, Voltage (Fuses)	
USA / Canada	120 V~, 60 Hz (T 3.15 A L 250 V)
UK / Australia / Europe	220-240 V~, 50/60 Hz (T 3.15 A L 250 V)
Korea / China	220-240 V~, 50/60 Hz (T 3.15 A L 250 V)
Japan	100 V~, 50/60 Hz (T 3.15 A L 250 V)
Power consumption @ ½ max power output	35 W
Mains connection	Standard IEC receptacle
Dimension / Weight	
Dimensions (H x W x D)	330 x 440 x 1385 mm (12.99 x 17.3 x 54.5")
Weight	15.8 kg (34.8 lbs)

*Independent of limiters and driver protection circuits.
**The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc., and any use of such marks by Music Group is under license.
***Average over stated bandwidth. Measured at 1 meter on axis.