

TWIN6 BE

Product Data Sheet

MADE IN
FRANCE

Twin6 Be is a 2.5-way monitor which offers transparency, an unmatched degree of definition and precision of the stereo image for this price category.



Key points

- Pure Beryllium inverted dome tweeter: very low directivity, excellent linearity and dynamics
- "W" composite sandwich cone: neutral sound, no distortion
- Protected Beryllium dome (the effect of the grille has been compensated on the amplifier to adjust the tonal balance).

Performance

Frequency response	40Hz - 40kHz
Maximum SPL	115dB SPL (peak @ 1m)

Electronic section

Inputs	Type / Impedance Connector Sensitivity	Electronically balanced / 10 kOhms XLR Adjustable, +4dBu or -10dBV
Bass Bass - Midrange Treble		150W rms, BASH® technology 150W rms, BASH® technology 100W rms, class AB
Power supply	Local supply Connection	230V (2A fuse) 115V (4A fuse) IEC inlet and detachable power cord
User controls and indicators		Input sensitivity selector Midrange driver selector (right/left) Adjustable tweeter and woofer levels by potentiometers On/off switch, voltage selector
Light indicator		Power On LED
Transducers		
Woofer		2 x 6W4370B, 6 ¹ / ₂ " (16.5cm) Focal "W" composite sandwich cone drivers
High frequency		TB871, Focal Beryllium inverted dome tweeter with protective grille
Shielding		Integral through cancellation magnets / cans or by magnet design
Cabinetwork		
Construction		7 ¹ / ₂ " (19mm) MDF panels
Finish		Dark red natural veneering side panels, black body
Dimensions (HxLxD)		9 ¹³ / ₁₆ " x 19 ¹¹ / ₁₆ " x 13 ³ / ₈ " (250mm x 500mm x 340mm)
Weight		30.8lb (14kg)