

# TWIN6

## Product sheet

MADE IN  
FRANCE

Twin6 is 2.5-way monitor offering transparency, a level of definition, dynamics and soundstage precision that is unrivalled in this price range. Thanks to its Focus full-range mode, Twin6 is two monitors in one, where the woofers alone become full-range speaker drivers.



### Key points

- Beryllium inverted dome tweeter: very low directionality, excellent linearity and dynamics
- Optimised baffle tweeter: excellent dispersion control
- Composite sandwich 'W'-cone: sound neutrality, no distortion
- Focus mode: two monitors in one; 2-way monitor and 1-way full-range monitor (woofer alone)
- Large laminar port: no port noises or distortion
- Automatic disengageable stand-by mode
- Settings: activatable/deactivatable, LF shelving, HF shelving, LMF @ 160Hz

Type	2.5-way monitor		
Frequency response (@ -3dB)	40Hz - 40kHz	User controls	Sensitivity, stand-by, Left/Right, HPF, LF Shelv, LMF EQ, HF Shelv
Focus mode	110Hz - 10kHz	Fuses	-100-120V, T3.15AL/250V -220-240V, T1.6AL/250V
Maximum SPL (Average CEA2034 50-10kHz free field @ 1m)	112dB	Bass	2 x 6.5" (16.5cm) "W" cone
Focus mode (Average CEA2034 100-10kHz free field @ 1m)	111.5dB	Treble	1.5" (38mm) Beryllium
Input	Balanced XLR 10 kΩ	Shielding	no
Bass amplifier stage	2 x 70W RMS	Construction	7/8" (22mm) MDF
Treble amplifier stage	50W RMS	Finish	Dark red natural veneering side panels, black body
Nominal power supply	-100-120 VAC/220-240 VAC 50/60Hz	Dimensions (HxWxD)	10 <sup>1/8</sup> x20 <sup>1/4</sup> x13 <sup>1/2</sup> " (25.8x51.4x34.4cm)
		Weight	48.5lbs (22kg)
		Temperature range	During use: 5-35°C In storage: 0-50°C