

Display		
Size	65 inch	86 inch
Response Time	8ms	6.5ms
Ratio	16:9	16:9
Display Area	1428.48 (H)×803.52 (V)mm	1428.48 (H)×803.52 (V)mm
Resolution	3840×2160	3840×2160
Pixel Pitch	0.372×0.372mm	0.4296×0.4296mm
Refresh Rate	60Hz	60Hz
Colour Depth	1.07B (10bit)	1.07B (10bit)
Colour Gamut (Typ.)	90% NTSC	90% NTSC
Contrast Ratio	1200:1	1200:1
Viewing Angle	178 (H/V)	178 (H/V)
Backlight Structure	DLED	DLED
Brightness (Typ.)	350cd/m2	350cd/m2
Lifespan	≥30,000 hours	≥30,000 hours
	Touch System	
Touch Principle	Infrared	
Touch Points	20 Points	
Supported Systems	Windows 10/Windows 8/Windows 7/Windows XP/Android/Linux/macOS X/Chrome	
Minimum Recognisable Object	2mm	
Touch Object	Finger, Stylus	
Response Time	≤10ms	
Touch Accuracy	±1mm	
	Speakers	
Channel	2.1	
Power	2×10W+20W	
	Microphone	
Quantity	6	
Voice Pickup Range	0~8	
	Camera	
Quantity	1	
Pixels	12MP	
Location	In the Middle of the Upper Bezel	
	Power	
Power Input	220V~ 50Hz 2.0A	
Maximum Power Consumption	440W	
Standby Power	≤0.5W	
	Environment	
Operation Temperature	0°C-40°C	
Operation Humidity	10%-90%RH	
Storage Temperature	-20°C-60°C	
Storage Humidity	10%-90%RH	
Altitude	≤5000 metres	

*Data are from MAXHUB laboratory