





**T4** 

# " IP65 SPEAKER, BLACK (PAIR) [100V|16Ω]



100V / 16Ω Input



Easy Install



Weatherproof



Bracket Included



Ver./Hor. Installation



Available in Black or White

The T4 two-way IP65 loudspeakers with built-in 100V transformer and  $16\Omega$  power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bar terraces, churches, malls or conferences. The speakers are housed in a stylish weatherproof plastic cabinet (IP65 - using the back cover) providing an excellent architectural integration, both indoor and outdoor. The very accurate speaker's coverage allows the people, among the audience, to perceive the sound in the same way. The low frequencies are reproduced by a 4" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. A U-bracket is included and will support your installation on the wall or ceiling.

P	rod	uc	t T	ΓVI	oe

2-Way Outdoor Passive Speaker (16Q/100V)

# **RMS Power**

40W

### Sensitivity (1W, 1m)

#### Low Frequency Driver

4" Woofer

### **Recommended Amplifier**

A200 | MX120 | MX350

### IP Rating

IP65

#### Net Weight

2.8kg (6.2lb)

### Frequency Response (-6dB)

75Hz - 20kHz

# **Program Power**

80W

### Maximum SPL (calculated)

107dB

### High Frequency Driver

0.8" Dome Tweeter

### Grille

Aluminum Acoustically Invisible

# Dimensions (WxHxD)

140 x 230 x 172mm (5.5 x 9 x 6.8 in)

### **Shipping Weight**

7kg (15.4lb)

### Nominal Coverage (-6dB)

120° H x 90° V

# **Nominal Impedance**

 $16\Omega$  (low impedance mode)

### Transformer Taps 100V

10W | 20W | 40W

#### **Input Connectors**

4 Pins Screw Connector (IN/OUT)

### Construction

Weatherproof Plastic Cabinet

### Fixation

Wall U-Bracket (included)

### Accessories

Ball-Joint Wall Bracket for T4 (not