





T₆W

6.5" IP65 SPEAKER, WHITE (PAIR) [$100V|16\Omega$]



100V / 16Ω Input



Easy Install



Weatherproof



Bracket Included



Ver./Hor. Installation



Available in Black or White

The T6 two-way IP65 loudspeakers with built-in 100V transformer and 16Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bar terrace, churches, malls or conferences. The speakers are housed in a stylish weatherproof plastic cabinet (IP65 - using the back cover) providing an excellent architectural integration, both indoor and outdoor. The very accurate speaker's coverage allows the people, among the audience, to perceive the sound in the same way. The low frequencies are reproduced by a 6" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. A U-bracket is included and will support your installation on the wall or ceiling.

| Pro | du | ct | Tv | pe |
|-----|----|----|-----|----|
| | | - | . 2 | P- |

2-Way Outdoor Passive Speaker (16 Ω /100V)

RMS Power

80W

Sensitivity (1W, 1m)

Low Frequency Driver 6.5" Woofer

0.0 1100101

Recommended Amplifier

MX120 | MX350

IP Rating

IP65

Net Weight

6.5kg (14.3lb)

Frequency Response (-6dB)

60Hz - 18kHz

Program Power

160W

Maximum SPL (calculated)

.....

High Frequency Driver

1" Driver

Grille

Aluminum Acoustically Invisible

Dimensions (WxHxD)

182 x 362 x 226mm (7.2 x 14.3 x 8.9 in)

Shipping Weight

15.6kg (34.4lb)

Nominal Coverage (-6dB)

100" H x 75° V

Nominal Impedance

16Ω (low impedance mode)

Transformer Taps 100V

20W | 40W | 80W

Input Connectors

4 Pins Screw Connector (IN/OUT)

Construction

Weatherproof Plastic Cabinet

Fixation

Wall U-Bracket (included)

Accessories

Hinged Wall Bracket for T6W/T8W (no included)