

TECHNICAL SPECIFICATIONS		NX 910-A	NX 912-A	NX 915-A
Acoustical specifications	Frequency Response:	50 Hz ÷ 20000 Hz	50 Hz ÷ 20000 Hz	45 Hz ÷ 20000 Hz
	Max SPL @ 1m:	130 dB	130 dB	131 dB
	Horizontal coverage angle:	100°	100°	100°
	Vertical coverage angle:	60°	60°	60°
Transducers	Compression Driver:	1.0", 1.75" v.c	1.0", 1.75" v.c	1.0", 1.75" v.c
	Woofer:	10", 2.5" v.c	12", 2.5" v.c	15", 2.5" v.c
Input/Output section	Input signal:	bal/unbal	bal/unbal	bal/unbal
	Input connectors:	Jack/XLR	Jack/XLR	Jack/XLR
	Output connectors:	XLR	XLR	XLR
	Input sensitivity:	+4 dBu	+4 dBu	+4 dBu
Processor section	Crossover Frequencies:	1600 Hz	1600 Hz	1600 Hz
	Protections:	Thermal, RMS limiter	Thermal, RMS limiter	Thermal, RMS limiter
	Limiter:	Soft limiter	Soft limiter	Soft limiter
	Controls:	2 way EQ, crossover filtering	2 way EQ, crossover filtering	2 way EQ, crossover filtering
Power section	Total Power:	2100 W Peak, 1050 W RMS	2100 W Peak, 1050 W RMS	2100 W Peak, 1050 W RMS
	High frequencies:	700 W Peak, 350 W RMS	700 W Peak, 350 W RMS	700 W Peak, 350 W RMS
	Low frequencies:	1400 W Peak, 700 W RMS	1400 W Peak, 700 W RMS	1400 W Peak, 700 W RMS
	Cooling:	Convection	Convection	Convection
	Connections:	VDE AC socket	VDE AC socket	VDE AC socket
Standard compliance	CE marking:	Yes	Yes	Yes
Physical specifications	Cabinet/Case Material:	Polyurea coated plywood	Polyurea coated plywood	Polyurea coated plywood
	Hardware:	6xM10 (2 Top, 2 Side, 2 Back)	6xM10 (2 Top, 2 Side, 2 Back)	6xM10 (2 Top, 2 Side, 2 Back)
	Handles:	1 Top	2 Side	2 Side
	Grille:	Steel	Steel	Steel
	Color:	Black	Black	Black
Size	Height:	510 mm / 20.1 inches	620 mm / 24.41 inches	705 mm / 27.76 inches
	Width:	294.2mm / 11.6 inches	361.4 mm / 14.2 inches	419.6 mm / 16.5 inches
	Depth:	332.3 mm / 13 inches	404.5 mm / 15.9 inches	450.4 mm / 17.7 inches
	Weight:	16.4 kg / 36.1 lbs	20.8 kg / 45.8 lbs	24.1 kg / 53.1 lbs