

bDRIVE *passive / active*



bDRIVE 10



DRIVE 12

moulded cabinets

lightweight and portable

24bit / 48kHz DSP on AP model

three carry handles on 12 and 15" models

multiple M10 flying points

AP model with delay, limiter, 3 band EQ, 4 cabinet modes

bDRIVE-10		bDRIVE-10A/AU/AP	
MAX SPL	124dB	MAX SPL	121dB
PEAK	1000W	AMP PEAK	1000W
PGM	500W	AMP PGM	500W
RMS	250W	AMP RMS	250W (200+50)
WEIGHT	13kg	WEIGHT	14kg
Cabinet type	2-way passive	Cabinet type	2-way active
Frequency response	60Hz - 20kHz	Frequency response	60Hz - 20kHz
Sensitivity 1w@1m	94dB	Input sensitivity	0dBu
Coverage (h x v)	90 x 60 degree	Coverage (h x v)	90 x 60 degree
Nominal Impedence	8 ohm	LF Driver	10" / 50mm VC
LF Driver	10" / 50mm VC	HF Driver	1.35" / 34mm VC
HF Driver	1.35" / 34mm VC	Crossover frequency	2.5kHz
Crossover frequency	2.5kHz	Connection	XLR/JACK input
Input connection	2 x 4-pole		XLR output
Dimensions (wxhxd)	335 x 545 x 319mm	Dimensions (wxhxd)	335 x 545 x 319mm



DRIVE *passive / active*



DRIVE 15SA



DRIVE 12AU Rear



DRIVE 12A Rear



DRIVE 15SA Rear

3 band EQ

AU models with built in USB/SDCARD media player

AU models with bluetooth playback

class D amplification on active models

cabinet angles for use as monitor

35mm top-hat on all models

	DRIVE-12	DRIVE-15		DRIVE-12A/AU	DRIVE-15A/AU	DRIVE-15SA
MAX SPL	126dB	127dB	MAX SPL	126dB	127dB	120dB
PEAK	1000W	1000W	AMP PEAK	1240W	1240W	1800W
PGM	500W	500W	AMP PGM	620W	620W	900W
RMS	250W	250W	AMP RMS	310W (250+60)	310W (250+60)	450W
WEIGHT	17.2kg	20.4kg	WEIGHT	17kg	20.2kg	25kg
Cabinet type	2-way passive	2-way passive	Cabinet type	2-way active	2-way active	active sub woofer
Frequency response	50Hz - 20kHz	45Hz - 20kHz	Frequency response	50Hz - 20kHz	45Hz - 20kHz	30Hz - 150kHz
Sensitivity 1w@1m	96dB	97dB	Input sensitivity	0dBu	0dBu	0dBu
Coverage (h x v)	80 x 40 degree	80 x 40 degree	Coverage (h x v)	80 x 40 degree	80 x 40 degree	-
Nominal Impedence	8 ohm	8 ohm	LF Driver	12" / 50mm VC	15" / 50mm VC	15" / 75mm VC
LF Driver	12" / 65mm VC	15" / 65mm VC	HF Driver	1.35" / 34mm VC	1.35" / 34mm VC	-
HF Driver	1.35" / 34mm VC	1.35" / 34mm VC	Crossover frequency	2kHz	2kHz	-
Crossover frequency	2kHz	2kHz	Connection	XLR/JACK input	XLR/JACK input	2 x XLR input
Input connection	2 x 4-pole	2 x 4-pole		XLR output	XLR output	4 x XLR output (fr + filt)
Dimensions (wxhxd)	390 x 630 x 360mm	450 x 710 x 370mm	Dimensions (wxhxd)	390 x 630 x 360mm	450 x 710 x 370mm	475 x 590 x 550mm

bDRIVE/DRIVE series