

GX *passive*



- durable MDF cabinets***
- strong steel front grille***
- hard wearing carpet covering***
- hard wearing paint finish***
- top hat on gx10/12/15m models***
- recessed carry handles***

	GX-10	GX-12	GX-15	GX-12M	GX-15M
MAX SPL	95dB	97dB	98dB	97dB	98dB
PEAK	600W	800W	1000W	800W	1000W
PGM	300W	400W	500W	400W	500W
RMS	150W	200W	250W	200W	250W
WEIGHT	10kg	16kg	21kg	16kg	21kg
Cabinet type	2-way passive	2-way passive	2-way passive	2-way passive	2-way passive
Frequency response	80Hz - 18kHz	60Hz - 18kHz	40Hz - 18kHz	60Hz - 18kHz	40Hz - 18kHz
Coverage (h x v)	90 x 60 degree	90 x 60 degree	90 x 60 degree	90 x 60 degree	90 x 60 degree
Nominal Impedence	8 ohm	8 ohm	8 ohm	8 ohm	8 ohm
LF Driver	10"	12"	15"	12"	15"
HF Driver	piezo	piezo	1.35" / 34mm VC	piezo	1.35" / 34mm VC
Crossover frequency	4kHz	4kHz	3kHz	4kHz	3kHz
Input connection	2 x 4-pole	2 x 4-pole	2 x 4-pole	2 x 4-pole	2 x 4-pole
Dimensions (wxhxd)	350 x 520 x 260mm	390 x 570 x 290mm	470 x 710 x 350mm	400 x 530 x 370mm	680 x 470 x 350mm

GX *active*



- two inputs with EQ on active models***
- balanced inputs***
- 4-pole extension socket to power passive speaker from an active model***
- trapezoidal cabinet design***

	GX-10A	GX-12A	GX-15A	GX-12MA	GX-15MA
MAX SPL	120dB	124dB	126dB	124dB	126dB
AMP PEAK	280W	560W	680W	560W	680W
AMP PGM	140W	280W	340W	280W	340W
AMP RMS	70W	140W	170W	140W	170W
WEIGHT	13kg	16kg	21kg	16kg	21kg
Cabinet type	2-way active	2-way active	2-way active	2-way active	2-way active
Frequency response	80Hz - 18kHz	60Hz - 18kHz	40Hz - 18kHz	60Hz - 18kHz	40Hz - 18kHz
Coverage (h x v)	90 x 60 degree	90 x 60 degree	90 x 60 degree	90 x 60 degree	90 x 60 degree
LF Driver	10"	12"	15"	12"	15"
HF Driver	piezo	piezo	1.35"/34mm	piezo	1.35"/34mm
Crossover frequency	4kHz	4kHz	3kHz	4kHz	3kHz
Connection	2 x XLR/JACK/RCA input XLR/JACK output 4-pole extension socket	2 x XLR/JACK/RCA input XLR/JACK output 4-pole extension socket	2 x XLR/JACK/RCA input XLR/JACK output 4-pole extension socket	2 x XLR/JACK/RCA input XLR/JACK output 4-pole extension socket	2 x XLR/JACK/RCA input XLR/JACK output 4-pole extension socket
Dimensions (wxhxd)	350 x 520 x 260mm	390 x 570 x 290mm	470 x 710 x 350mm	400 x 530 x 370mm	680 x 470 x 350mm