

SENSE *monitor speakers*



SENSE 12A (carpet finish)

SENSE+ *monitor speakers*



SENSE 15A+ (paint finish)

coaxial design

hard wearing carpet or durable paint finish models

24bit / 48kHz DSP on active models

43 degree monitor angle

35mm top hat socket

live or monitor modes on DSP with 3-band EQ

ultra compact footprint

neodymium HF components

high performance class D amplifiers

use for monitoring or as PA cabinet

strong steel front grille

12" or 15", active or passive models

	SENSE12/12+		SENSE12A/12A+
MAX SPL	126dB	MAX SPL	127dB
PEAK	1000W	AMP PEAK	1200W
PGM	500W	AMP PGM	600W
RMS	250W	AMP RMS	300W (260+40)
WEIGHT	14.5kg	WEIGHT	15kg
Cabinet type	2-way coaxial passive	Cabinet type	2-way coaxial active
Frequency response	55Hz - 20kHz	Frequency response	55Hz - 20kHz
Sensitivity 1w@1m	96dB	Input sensitivity	0dBu
Coverage (h x v)	80 x 80 degree	Coverage (h x v)	80 x 80 degree
Nominal Impedance	8 ohm	LF Driver	10" / 65mm VC
LF Driver	12" / 75mm VC	HF Driver	1.75" / 44mm VC
HF Driver	1.75" / 44mm VC	Crossover frequency	2.4kHz
Crossover frequency	2.2kHz	Connection	2 x XLR/JACK input + 3.5mm
Input connection	2 x 4-pole		XLR output
Dimensions (wxhxd)	400 x 436 x 323mm	Dimensions (wxhxd)	335 x 545 x 319mm



	SENSE15/15+		SENSE15A/15A+
MAX SPL	128dB	MAX SPL	128dB
PEAK	1200W	AMP PEAK	1200W
PGM	600W	AMP PGM	600W
RMS	300W	AMP RMS	300W (260+40)
WEIGHT	18.8kg	WEIGHT	20.5kg
Cabinet type	2-way coaxial passive	Cabinet type	2-way coaxial active
Frequency response	55Hz - 20kHz	Frequency response	55Hz - 20kHz
Sensitivity 1w@1m	97dB	Input sensitivity	0dBu
Coverage (h x v)	80 x 80 degree	Coverage (h x v)	80 x 80 degree
Nominal Impedance	8 ohm	LF Driver	15" / 75mm VC
LF Driver	15" / 75mm VC	HF Driver	1.75" / 44mm VC
HF Driver	1.75" / 44mm VC	Crossover frequency	2.4kHz
Crossover frequency	2.2kHz	Connection	2 x XLR/JACK input + 3.5mm
Input connection	2 x 4-pole		XLR output
Dimensions (wxhxd)	460 x 510 x 377mm	Dimensions (wxhxd)	460 x 510 x 377mm